

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

(2)



(19)

(11) Publication number: 0.

Generated Document.

JP03111522A2

## PATENT ABSTRACTS OF JAPAN

(21) Application number: 01246308

(51) Intl. Cl.: C22C 1/02 C23C 26/00 F04C

(22) Application date: 25.09.89

(30) Priority:

(43) Date of application  
publication:

13.05.91

(84) Designated contracting  
states:

(71) Applicant: HITACHI LTD

(72) Inventor: YAMAMOTO AKIHIKO  
YAMADA TOSHIHIRO  
OKADA RYOJI  
IBARAKI YOSHIKI  
OKAMOTO JOJI

(74) Representative:

**(54) PRODUCTION OF  
SLIDING PARTS OF  
ALUMINUM OR  
ALUMINUM ALLOY**

(57) Abstract:

**PURPOSE:** To inexpensively and speedily produce a sliding member having excellent wear resistance and high long-term reliability by subjecting the sliding part of Al or Al alloy to a rapid melting and rapid resolidifying treatment with a high density energy and providing numerous pores on the surface layer.

**CONSTITUTION:** The sliding part of the Al alloy 6 of an Al-Si system, etc., where the above-mentioned Al alloys slide with each other or the Al alloy and cast iron, etc., slide each other is irradiated with a laser 8 of high density energy and is thereby subjected to the rapid melting and rapid resolidifying treatment. A surface layer 7 provided with

numerous pores is formed on the surface layer of the above-mentioned Al alloy 6 in this way. The foregoing formation of Ni plating on the surface of the above-mentioned Al alloy 6 and the formation of the corrosion resistant Ni-Al alloy layer in the hole parts by the laser 8 are possible as well. The treating of the surface 7 is thereafter finished by machining or grinding to expose the pores. The lubricating condition of the sliding part is improved in this way, by which the breakage of oil films is prevented and the seizure resistance is improved; in addition, the hard alloy is formed on the surface and the wear resistance is thereby improved.

COPYRIGHT: (C)1991,JPO&Japio

